

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - A.R. Flint; L. L. Williams, under Contract #151 dated May 23, 1871 (DCSO records, Vol. 13 Page 5685)

Set post to ¼ sec. corner (on steep rocky hill sloping West, heavy Fir timber)

A Fir 8" dia., bears N.85°W., 18 lks. dist.

A Fir 18" dia., bears N.25°E., 16 lks. dist.

Claude Kerr, Logging Engineer, July 1950 (Could find no record source for this renewal)

I found Fir BT bearing N.25°E., for 16 lks. I chopped down to old face and found the scribe markings reading ¼ S BT. This BT is now a 24" solid snag about 12" high and is just below a 10 ft. high rock bluff.

The other BT is gone.

I put a new 4" x 4 ft. Fir limb post in for the corner and also put my cruiser mark "K" on the BT.

Doug. County Surveyors Office - James Byron, Deputy - John Powell; Dale McFarland - Dec. 1961 - C.S. File 49/64-42

Found - Orig. 12" now 24" Fir snag, N.25°E., 10.6 ft., previously opened, shows good scribing "¼".

NW BT not found.

Set brass cap at cor. mkd: County Surveyor's Office, 1961

¼ S23|S24 T28S R5W

New BT - 38" R.Fir bears S.63°E., 78.3 ft. bark scribed "¼" S24 CS BT".

Set PK in rock outcrop on top of point 6 ft. above ground, bears N.67°E., 5.6 ft.

Brass cap at foot of 10 ft. high rock bluff which is in last group of rock bluffs going North along section line.

BLM resurvey by Peterson and Bedell, under Group #1425, Survey, April 1988-April 1990 (DCSO records, Vol. 49 Page 18701)

The ¼ sec. cor., perpetuated and recorded by Byron, in 1961, from original evidence no longer in existence, monumented with an iron post, 1 in. diam., firmly set, projecting 3" above ground, with properly mkd. brass cap.

from which a bearing object set by Byron:

A PK nail, in the westerly face of a rock bluff, bears N.63½°E., 9 lks. dist., (The nail is 6 ft. above the base of the bluff.)

and a new reference monument:

(Cont. Next Page)

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A brass tablet, 3¼" dia., with a 3½" stem cemented into the high point of a rock outcrop, 12 x 5 x 4 ft. high bears S.22°W., 20.9 lks. dist., mkd. RM ¼ S23 13.8 ft. 1988 and an arrow pointing to the corner.

Found Brass cap, Aug. 1990, M 110-57

Kristian DeGroot - For: Jesse Family LLC - Oct 2012 - M157-64

LAT: 43°07'12.90399" N LONG: 123°14'44.68145" W.
Found a 1961 BCIP by J. Byron per C.S. 49/64 and accessories per 1988 USBLM dependent resurvey by D. Bedell & B. Peterson.