

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5658)

Set post corner to secs. 11, 12, 13 and 14, from which
A Y.Oak 14" dia., bears S.72½°W., 149 lks. dist.
A Y.Oak 12" dia., bears N.20°W., 208 lks. dist.
A W.Oak 15" dia., bears N.10°E., 406 lks. dist.
A Laurel 12" dia., bears S.35 3/4°E., 595 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - S. Bilow; M. Godfrey - Nov. 1957 - C.S. File 49/21-52 & M8-3

No original BTs found. Position of corner determined by calls. Survey of Section 12 and tie to ¼ corner 11 & 14. See C.S. File 46/111.

Set Brass cap at fence cor. mkd: S11|S12 T28S R5W
S14|S13 County Surveyor's Office, 1957

New BTs -14" W.Oak, West 39.6 ft. scribed T28S R5W S14 CSBT
9" W.Oak, N.40°W., 58.6 ft. scribed T28S R5W S11 CS BT.
6" Apple, N.85½°E., 7.7 ft. scribed T28S R5W S12 CS BT.
16" W.Oak bears S.27½°E., 290.4 ft. scribed T28S R5W S13 CS BT.

Fd BC & 2 BTs By H Johnstone, 2/1980 - C.S. File 58/175-2

Found OK by C. Sweeden, May 2001 - M138-20

Kristian DeGroot - For: Jesse Family LLC - Oct 2012 - M157-64

LAT: 43°08'31.34081"N. LONG: 123°14'45.44985"W.
Found a 1957 DCSO BCIP and accessories of record by J. Byron per C.S. 49/21 & M 8-3.