

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5660)

Set ¼ sec. post, from which
 A W.Oak 15" dia., bears S.65°E., 96 lks. dist.
 A Y.Oak 12" dia., bears N.39°W., 127 lks. dist.
James Gilmore's house bears S.49¼°E., 100 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - M. Godfrey; S. Bilow. - Nov. 1957 - C.S. File 49/21-55

No original BTs found.
(See C.S. File for method used to determine position of this corner.)
Set brass cap at cor. mkd: ¼ S11|S12 T28S R5W Co. Surv. Office, 1957
New BTs -12" W.Oak bears S.75°W., 162.0 ft. scribed ¼ S11 CS BT.
 20" Cherry bears S.81½°E., 490.2 ft. scribed ¼ S12 CS BT.

Doug. County Surveyors Office - James Byron & Crew - Nov. 15, 1962 - C.S. File 49/64-80

Found - Brass cap at corner and SW BT. as recorded.
 SE BT now down.
Set - ¾" I.Rod under N-S fence and on line between brass cap and S.75°W. BT. ¾" I.R. bears S.75°W., 41.3 ft. from ¼ corner.
New BT - 28" W.Oak bears S.16°W., 342.3 ft. scribed ¼ S11 CS BT.

Doug. County Surveyors Office - Gary Langlitz, Deputy - Stephen J. Flause - Feb. 23, 1977 - C.S. File 59/29-32

Monument set by survey in 1957 and found in 1962, not found at this time.
Found - 12" now 16" For of W.Oak, 30" dia. tree at base, alive with well healed double blaze.
 The SE bearing tree noted in 1957 has been destroyed.
 28" now 30" W.Oak alive with well healed double blaze.
 A ¾" I.Rod set in a N-S fenceline.
Set - In accordance with the found accessories, We Set a 1" x 30" I.P. buried 12" below ground level, with brass cap attached mkd:
(Cont. Next Page)

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyor T28S R5W
1977 S11|S12
 $\frac{1}{4}$

from which
A 16" For of a W.Oak bears S.74°W., 162.0 ft. (Rec. S.75°W., 162.0 ft.)
3/4" I.Rod bears S.74°W., 41.3 ft. (Rec.S.75°W., 41.3 ft.)
30" W.Oak bears S.16°W., 340.7 ft. (Rec. S.16°W., 342.3 ft.)
Corner located in open pasture, both BTs are westerly of Tucker Creek.

Doug. County Surveyors Office - Larry E. Monrean, Deputy - R.W. Smith; P. Bair - Nov. 9, 1983 - C.S. File 62/9-15

Found - Iron pipe and 1977 brass cap, properly mkd., firmly set 12" below ground level.
12" now 15" east fork of double forked W.Oak bears S.75°W., 163.5 ft. (Rec. 162.0 ft., is to face of BT) BT has well healed double blaze.
28" now 29" W.Oak bears S.16°W., 342.3 ft.. BT is tipped out and down. BT will be cut in near future.
3/4" I.Rod bears S.75°W., 41.6 ft. (Rec. 41.3 ft., protruding 4" above ground in N-S fence line.

New Accessories:
13" multiple topped B.Oak double blazed & scribed " $\frac{1}{4}$ S11 CS BT" bears N.69E., 329.6 ft.
A 5/8" I.Rod with alum. cap stamped "B0" set 2" below ground, bears S.9°E., 254.8 ft. I.R. is 1 ft. east of NE concrete footing block of barn.
Monument lies in open pasture 41 ft. East of N-S fence and 252 ft. North of barn. Metal detector may be helpful in locating buried corner. See sketch in C.S. File)

Fd BC, IR & 1 BT By H Johnstone, 2/1980 - C.S. File 58/175-2
Found OK by C. Sweeden, May 2001 - M138-20