

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5661)

-----  
Set ¼ sec. post, from which  
    A W.Oak 18" dia., bears S.84°06'E., 930 lks. dist.  
Made trench, no other trees near.  
The NE cor. of Otey Boon's and the SE cor. of M. Adam's  
claims bears N.87°21'E., 853 lks. dist.  
J.N. Barker's house bears N.74¼°E.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow - Nov. 1957 - C.S. File 49/21-56 & M 8-3

-----  
Set corner by proportional measurement.  
Set Brass cap at corner mkd. ¼ S1|S1 T28S R5W County Surveyor's Office, 1957.  
NW Corner of brick house bears S.40°15'W., 57.4 ft.  
NE corner of house bears S.21°E., 47.1 ft.  
Found boat spike set by County Road Engineers for road intersection, bears N.0°30'W., 31.9 ft.  
No suitable trees near for bearing trees.

Found OK, Oct. 1989, Donald Bentz, M 109-11  
Fd as per record-5/2020 - by R Badgley - M176-77