

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 25 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - A.R. Flint & L.L. Williams under Contract #151 dated May 23, 1871 (DCSO records, Vol. 13 Pg. 5684)

-----  
Set post to 1/4 sec. corner, from which  
A Fir 15" dia., bears S.45°E., 18 lks. dist.  
A Fir 20" dia., bears N.45°W., 57 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - Dec. 1961 - C.S. File 49/64-51

-----  
Found - Orig. 20" now 44" R.Fir, shows good bark scribing "BT", N.45°W., 37.6 ft.  
Orig. SE BT not found.  
Set Brass cap mkd: County Surveyors 1/4 S25 T28S R5W  
Office, 1961 S36  
New BTs -Rescribe orig. now 44" R.Fir N.45°W., 38.4 ft. "1/4 S25 CS BT". (bark scribe)  
18" R.Fir bears S.61°E., 37.0 ft. scribed 1/4 S36 CS BT.

Found OK, Burton Holt, April 1981, M 87-56

Found 1961 Cap, Orig. NW BT, and Byron's SE BT, BLM resurvey by Bedell & Peterson, 1988-1990, (DCSO records, Vol. 49 Page 18697)

Douglas County Surveyors Office - Randall Smith & Stephen Flause - Oct. 14, 93 - C.S. 64/47-6

-----  
Monuments Fd.  
2 1/2" dia. DCSO brass cap on a 1 1/2" O.D. iron pipe protruding 12" above grd. (1961 DCSO)  
County Surveyors Office  
T 28 S R 5 W  
1/4 S 25  
S 36  
1961

Accessories Fd.  
20" now 44" dia., 45' charred D.Fir snag, single healed scar visibly, bark scribing from 1961 DCSO ren. burnt off, bears N.45°W., 38.4' (agrees with 1961 DCSO ren, Orig dist and 1988 BLM of 37.6' is a probable face measurement) OBT.  
18" now 25" dia., D.Fir with charred bark no blaze visible, bears S.61°E., 37' (agrees with 1961 DCSO ren., 1988 BLM dist. of 36.3' is a probable face measurement) 1961 DCSO (note tree is alive).

(Cont. Next Page)

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 cor. secs. 25 & 36

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

New Accessories  
9" D.Fir, double blazed and scribed "¼ S36 CS BT", bears  
S.20½°E., 87.1'.  
42" D.Fir, double blazed and scribed "¼ S25 CS BT", bears  
N.32°W., 169.3'.  
Corner lies approx 200' west of a NW-SE running creek on a  
steep easterly slope, in an old logged and wild fire burn  
area.

Fd. BC 4/2022 - Bart Heichel - M180-80  
Fd. BC 12/2023 - Bart Heichel - C.S. File 65/112-3