

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, and L.L. Williams Under Contract #151, dated May 23, 1871 (DCSO records Volume 13 Pages 5686)

-----  
Set post to ¼ sec. corner, from which  
    A maple, 6" dia., bears S.75°W., 48 lks.  
    A fir, 24" dia., bears N.75°E., 36 lks.

Douglas Co. Surveyors Office - V.R. Tracey - Feb. 1970 - C.S. File 49/64-83

-----  
Not found. Logged several years ago - No OBTs found.

Kristian DeGroot - For: Jesse Family LLC - Oct 2012 - M157-64

-----  
LAT: 43°07'39.41536" N.                      LONG: 123°14'09.39428" W.  
No evidence of the original corner. At the proportioned position:

Set - A 5/8" X 30" iron rod, 24" in the ground in a 36" diam. stone mound to top, with a 2" aluminum cap marked:

T28S R5W

¼  $\frac{S13}{S24}$

2012

PLS 1941

from which new BTs:

- A 23" D.Fir bears S.80°E., 62.2 ft scribed "¼ S24 BT"
- A 11" D.Fir bears S.52°30'E., 59.9 ft scribed "¼ S24 BT"
- A 16" D.Fir bears S.88°30'W., 13.9 ft scribed "¼ 13 BT"
- A 13" D.Fir bears N.41°30'W., 14.7 ft scribed "¼ S13 BT"