

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. cor. 24 & 25; 19 & 30, T28-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - James E. Freeman, under Contract #1 dated May 28, 1851 (DCSO records, Vol. 13 Pages 5602-03)

Set post cor. to secs. 19, 24, 25, & 30, from which
A Pine, 18" dia., bears N.88°E., 60 lks. dist.
A Redwood 24" dia., bears S.58°E., 52 lks. dist.
A Pine 30" dia., bears S.62½°W., 81 lks. dist.
A Pine 12" dia., bears N.16°W., 250 lks. dist.

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5611)

Set new post as per instructions, bearing trees all standing viz:
Pine 18" dia., bears N.80°E., 60 lks.
Cedar 24" dia., bears S.58°E., 52 lks.
Pine 30" dia., bears S.62½°W., 81 lks.
Pine 12" dia., bears N.16°W., 250 lks.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - Aug/Sept. 1961 - C.S. File 49/67-26

Found - Orig. 18" now down & mostly rotted Pine. We find good scribing "19 SR4W" on old section. BT bears N.88°E., 39.6 ft.
Orig. SE BT, down. No trace of NW or SW BTs.
1¼" I.P. 2 ft. North of corner. N-S wire fence is West of cor.
Set brass cap at cor. mkd: County Surveyor's S24|S19 T28S
Office, 1961 R5W S25|S30 R4W
New BTs - 16" Cedar bears S.24°E., 10.5 ft. scribed S30 T28S R4W CS BT.
10" Pine bears N.54°E., 6.7 ft. scribed S19 T28S R4W CS BT.
11" Cedar bears S.14°W., 11.2 ft. scribed S25 T28S R5W CS BT.
10" Pine bears N.45°W., 22.7 ft. scribed S24 T28S R5W CS BT.

BLM resurvey by G. Steven Popken, under Group #837 - Survey, June-July 1974 (DCSO records, Vol. 37 Pages 15361-62)

Found 1961 DCSO brass cap, from which the remains of the orig. bearing trees:
A root hole, bears N.80°E., 60 lks. dist., with a down pine alongside 16" dia., with fragmentary scribe marks visible on burned blaze.
(Cont. Next Page)

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. 24 & 25; 19 & 30, T28-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A root hole bears S.58°E., 52 lks. dist. with a down cedar alongside, 20" dia., no marks visible.
and the remains of bearing trees mkd. by Bryon
A pine snag 10" dia., bears N.54°E., 10 lks. dist.
with scribe marks T28S R4W S19 CS BT visible
on open double blaze.
A cedar snag 17" dia., bears S.24°E., 16 lks. dist., with
scribe marks T28S visible on open and burned blaze.
A cedar snag 11" dia., bears S.18°W., 17 lks. dist.,
with scribe marks T28S R5W S25 CS BT visible on
open double blaze.
A pine 10" dia., bears N.45°W., 36 lks. dist., with scribe
marks T S visible on open double blaze.
and new bearing trees
A pine 15" dia., bears S.47°W., 77 lks. dist. mkd.
T28S R5W S25 BT.
A pine, 11" dia., bears N.54°W., 105 lks. dist., mkd.
T28S R5W S24 BT.