

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 040060

PRIMARY CORNER DESCRIPTION E SE Cor. I. M. Arrington DLC #40

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, under Contract #28, dated April 20, 1854

Set a stone post 18 x 8 x 6, from which
A B.Oak 14" dia., bears N.67°W., 142 lks.

Doug. County Surveyors Office - James W. Byron; Milo Godfrey; S. Bilow - March 31, 1958 - C.S. File 49/73-1

Found - Orig. 14" now 26" B.Oak BT N.67°W., 93.7 ft. This BT recently opened, shows good scribing "T28 CL 40 R6 BT"

Stone set for corner not found.

Set Brass cap at cor. mkd: S. E. DLC 40 T28S R6W
County Surveyor's Office, 1958

New BTs - 26" Cedar N.29°W., 20.4 ft. scribed T28S R6W SE
CL 40 CS BT.

22" R.Fir S.7°W., 33.2 ft. scribed T28S R6W
SE CL 40 CS BT.

Fence corner bears N.61°W., 22 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 11/12/2002 - C.S. File 66/48-6

Found - 1958 DCS0 brass cap iron pipe protrudes 11" out of ground.

14" now down & rotted B.Oak no scribing fd. bears N.67°W., 93.7 ft. (OBT)

26" now 43" dia., I.Cedar with a fully healed double blaze bears N.31°W., 20.4 ft. (rec. N.29°W., 20.4 ft.) (1958)

22" now 35" dia., D.Fir with a fully healed double blaze bears S.7°W., 32.0 ft. (rec. S.7°W., 33.2 ft.) (1958)

Compass decl. 17½°E.

New - 7" dia., I.Cedar double blazed & scribed "ESE DLC 40 CS BT" bears S.50°E., 16.3 ft.

13" dia., W.Oak double blazed & scribed "ESE DLC 40 CS BT" bears N.89½°E., 51.0 ft.

Corner lies along westerly edge of a N-S running draw.