

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 043020

PRIMARY CORNER DESCRIPTION NW Cor. Smith DLC #43

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, under Contract #28 dated April 20, 1854  
-----  
Set post in prairie. Deposited stone 6 x 5. Raised mound with trench as per instructions.

Doug. County Surveyors Office - Vernon Tracy; and crew. Dec. 22, 1966 - C.S. File 49/139-115  
-----  
Found - DCSO brass cap, properly mkd., 4" above ground on S. side of driveway. (Recorded in Meadowbrook, Plat 9/24)  
No BTs available.  
Power Pole bears N.26°W., 20.8 ft. alum. tag 2"x6" mkd. "CopCo B9277".  
Power Pole bears N.66°W., 113.8 ft. alum. tag 2"x7" mkd. "CopCo B12467".  
Corner lies S.75°E., 251.0 ft. from business Rt. #99 (old Hwy) east edge of road surface, parallel to south edge of driveway.  
(Note: I could not find the source for the "set" BC. Looked through numerous field notes for the era of time - was not "set" on plat of Meadowbrook, but "found". V.L.)

Fd. BC, Eugene A. Bloom, Oct. 1985, M 99-57

Richard Bath, L.S. #1069 - For: Pacificorp & John Bell Logging - March 1995 - M 122-2 - C.S. File 63/163  
-----  
At the NW cor. of DLC #43 the 2 power poles that previously referenced the corner have been replaced, the poles are placed in different positions from the orig. poles, but have the same pole numbers. The new measurements, from the brass cap are:  
Power pole, mkd: "PPL B9277", bears N.28°10'W., 21.18'  
Power pole, mkd: "PPL B12467", bears N.68°12'W., 118.21'  
Distances were measured to a nail & shiner on the southerly face of each pole, approximately 1 ft. above ground level. The brass cap is 0.3 ft. northwest of the northwest corner of a 6 ft. high chainlink fence, and flush with the concrete footing.

FD. Brass cap Neil Hibbs, 3/2001 - M132-80  
Fd. Ok by Carl Sweeden, 10/2007 - M155-60  
Fd. DCSO BC per 1995 renewal, K. DeGroot - 6/2014 - M166-12