

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. 30 & 31; & 25 & 36, T28-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5696)

Set post cor. to secs. 25, 30, 31 and 36, from which
A Y.Oak 16" dia., bears S.27°W., 92 lks. dist.
A W.Oak 28" dia., bears S.71¼°E., 338 lks. dist.
A W.Oak 24" dia., bears N.14½°E., 259 lks. dist.
A Y.Oak 30" dia., bears N.14¾°W., 330 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; S.A. Bilow - Nov. 17, 1958 - C.S. File 49/50-14

Found - Orig. 40" now 42" Oak snag S.80°W., 73.9 ft. center rotted, no scribing found.
Orig. 28" now 36" Oak, down, S.71¼°E., 223.1 ft. center & most of tree rotted, no scribing fd.
No trace of other BTs found.

Set brass cap at cor. mkd: County Surveyors Office, 1958
S.E. Corner DLC 58 S25|S30 T28S
 R7W S36|S31 R6W

Fence corner 3.0 ft. West.

New BTs - 38" B.Oak bears N.44½°E., 206.6 ft. scribed S30 T28S
 R6W CS BT.
 12" Laurel bears West 47.5 ft. scribed S25 T28S
 R7W CS BT.
 12" W.Oak bears S.61½°E., 12.2 ft. scribed S31 T28S
 R6W CS BT.
 12" Laurel bears South 9.0 ft. scribed S36 T28S
 R7W CS BT.

Statement by J. Harold Nichols: "I have known the 42" Oak snag used on this date to determine the position of the section corner, to be a bearing tree, and that I saw scribing on this BT years ago."