

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Cor. Secs. 18, 19; Secs. 13 & 24 T28-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5694)

-----  
Set post cor. to secs. 13, 18, 19 and 24, from which  
An Ash 28" dia., bears N.70°E., 5 lks.  
An Ash 14" dia., bears S.60°E., 6 lks.  
A Maple 12" dia., bears S.65°W., 36 lks.  
An Ash 18" dia., bears N.44½°W., 126 lks.

Fritz Ingram, for: John Patrick - July 1973 - C.S. file 56/14

-----  
Set 5/8" Iron rod at sec. cor. by single proportion.

Doug. County Surveyors Office - Ray Tracy; J. Heritage - July 1973 - C.S. File 56/34-10

-----  
Found - Iron rod as set by Ingram. We remove I.R. and at the same location: SET 1" I.P. and brass cap mkd:

COUNTY SURVEYORS 13|18  
Office 1973 T28S R7W 24|19 T28S R6W

New BTs- 48" Cottonwood S.46½°W., 15.0 ft. mkd. T28S R7W S24 CS BT.  
12" Maple N.34°W., 19.2 ft. mkd. T28S R7W S 13 CS BT.  
18" Maple N.65°E., 143.6 ft. mkd. T28S R6W S18 CS BT  
20" Cottonwood S.13½°E., 41.5 ft. mkd. T28S R6W S19 CS BT.

We find no trace of original BTs.

Max Hull - For: Bob Griffis - April 1982 (added to corner report 7/26/2001) - M92-4 & C.S. File 58/179-5B

-----  
NE Sec. Cor. (sec. 24)  
Found 1973 County Surveyor brass cap N.0°37'12"E., 30.35 ft. from proportioned distance location.

Doug. County Surveyors Office - Karen Reed; Terrie Plouff May 11, 1982 - C.S. File 61/36-8

-----  
Found - 1" dia. I.P. set firmly in the ground protruding 0.9 ft. above ground with brass cap.  
48" dia. cottonwood bearing S.46½°W., 15.0 ft. with visible scribe "28S 7W S2 S BT" in a partially healed single blaze.  
12" dia. Maple (easterly fork of double trunk tree) bears N.34°W., 19.2 ft. with visible scribe "28S R7W S13 CS BT" in double blaze.

(Cont Next page)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

18" dia. Maple now 19" (southerly fork of a double trunk tree) bears N.65°E., 143.6 ft. with visible "T28S R6W S18 CS BT" in a single blaze.

20" Cottonwood now 22" down tree with visible scribe "28 R" in a single blaze. The stump bears S.13½°E., 41.5 ft. Place boat spike in stump at record bearing at a dist. of 40.9 ft.

No original BTs found.

Set - New corner by calculating correct position from survey by Ingram 1973. New position bears S.2°W., 29.8 ft. from fd. monument. Remove cap from 1973 monument, leave pipe in place and drive yellow plastic cap mkd. "Douglas County" into pipe.

A 1" x 36" I.P. with brass cap stamped "Douglas County Surveyor T28S S13 S18 S24 S19 R7W R6W 1982", firmly in the ground protruding 0.2 ft. (new position bears S.2°W., 29.8 ft. from 1973 pipe)

New bearing and distances:

- 12" Maple bears N.9°W., 46.1 ft.
- 19" Maple bears N.62°E., 158.9 ft.
- 48" Cottonwood bears N.22½°W., 21.7 ft. rescribe T28S R7W 13 CS BT" in double blaze. Deface other blaze.

New BT - 47" Cottonwood bears S.44°E., 3.1 ft. to boat spike set above fencing. (Impracticable to scribe)

No suitable trees in SW quadrant.

Cor. located S'ly side of dim road, 2 ft. north of E-W fence.

---

Doug. County Surveyors Office - Randall Smith; Stephen Flause  
August 29, 1984 - C.S. File 62/21-27

-----

CORNER REPORT ONLY

Found - 1982 County brass cap on a I.P. flush with ground.

- 12" double trunked Maple with visible scribing in partially healed blaze on East for "S R 7 W S13 CS" bears N.11½°W., 46.1 ft. (Rec. N.9°W., 46.1')
- 19" now 20" Maple with visible scribing in a partially healed single blaze "T28S R6W S18 CS BT" bears N.56°E., 159.8 ft. (Rec. N.62°E., 158.9ft.) is to southerly maple of two maples which root crowns have grown together.
- 48" now a 46" Cottonwood with visible scribing in a partially healed double blaze "28S R7W S13 CS BT" bears N.25°W., 21.7 ft. (Rec. N.22½°W)
- 47" now 43" Cottonwood with a boat spike 6 ft. above ground. Spike bears S.47°E., 3.1' (Rec. S.44°E)

I.P. not fd. Probably removed when field was plowed.

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Cor. Secs. 18, 19; Secs. 13 & 24 T28-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause  
- Oct. 9, 1997 - C.S. 64/78-10

-----  
Found - No monument of record found.  
Alum. nail and a hub tack  
Brg's. & Dist. taken from found Alum. nail  
12" Maple, bearing N.9°W., 46.1' per 1982 renewal  
is now gone.  
19" now double trunked Maple, with a fully healed  
single blaze on 23" dia. southerly trunk root  
crown of southerly trunk, bears N.56°E., 159.8'  
(agrees with 1984 record.) 1982  
48" now 46" dia. Cottonwood, with a fully healed  
double blaze, bears N.22½°W., 21.7' (agrees  
with 1982 record) 1982.  
47" now double trunked Cottonwood, with a 46" dia.  
westerly trunk, bears S.60°E., 5.1' to center  
of root crown (rec. S.47°E., 3.1' is to a boat  
spike that was not found (we single blaze and  
scribe T28S R6W S19 CS BT). 1982

Note: rec. brg. & dist. from nail goes to bark of tree  
rec. brg. & dist. from H&T is short of tree.

Set - 2 3/8" brass cap on a 1 3/8" O.D. by 32" long iron  
pipe is set at position of found nail. BC/IP  
protrudes 4" above ground.

Douglas County Surveyors

T 28 S

R S 13 | S 18 R

7 S 24 | S 19 6

W 1997 W

OFFICE

18" dia. Maple, single blazed "T28S R6W S18 CS  
BT", bears N.9½°E., 132.8'.

DCS0-GIS Corner visitation - 7/12/2004 - Typed: 1/31/2011 -  
C.S. File 67/33-1

-----  
Monument - BC/IP - 1.25"  
Comment - (needs) rehab

Fd. Ok by D. Beedle - 1/2005 - M147-16