

PRIMARY CORNER DESCRIPTION NW Cor Sec 6; NE Cor Sec 1 T28-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Surveyed by Robert Elder & Henry S. Gile, Deputy Surveyors, under contract #31, dated April 7, 1853. (DCSO records Vol. 12 Page(s) 5159)


-----

Set post cor. to Tp. 28 S., and between Rs. 6 & 7 from which:  
 A Y.Oak, 16" dia. bears S.57½°E., 70 lks. dist.  
 A Y.Oak, 14" dia. bears S.24½°W., 75 lks. dist.

U.S.G.L.O. Resurvey of North boundary T.28 S., R.7 W. (6th standard parallel) 1924 by Mensch. (DCSO records Vol. 14, pg. 5833 and page 5864)

-----

I commence at the standard cor. of Tps 28 S Rs 6 & 7 W established by Elder and Gile in 1853, the point for which is located by record bearing & distance from the SW original BT Found - A Black Oak, 24" dia. bears S.24½°W., 75 lks. dist. blazes open and marks legible. I re-mark this tree "SC T28S R7W S1 BT"  
 SE Bearing tree has rotted away, but stump hole indicating its position, bears S.57½°E., 70 lks.  
 Set an iron post, 3 ft. long, 3" dia. 27" in the ground with brass cap marked:



New - A B.Oak, 6" dia. bears S.36°E., 61 lks. marked: SC T28S R6W S6 BT.

Douglas Co. Surveyors Office - Randall W. Smith, Stephen J. Flause; June 16, 1993 - C.S. File 64/46-5

-----

Found - 3¼" dia. Brass Cap on a 3" O.D. iron pipe, protruding 9" above ground. (1924 GLO)  
 14" now 25" dia. B.Oak with a previously opened blaze, hollowed out center, no scribing visible, bears S.24½°W., 49.5 ft. (orig. BT)  
 Orig. SE BT now gone  
 1924 GLO renewal SE BT now gone.  
 BTs not of record, tags dated 2/61 posted by C-S.  
 8" dia. pistol butt dead Madrone, with a partially healed upper blaze, no scribing visible, healed lower blaze, bears S.27°E., 5.0 ft. to root crown. BT tag record S.20°E 4.5 ft. Bearing hits upper blaze.

continued next page

