

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 131700

PRIMARY CORNER DESCRIPTION South ¼ Cor. for S. 31 only, T27-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set ¼ sec. post, from which  
A Y.Oak, 24" dia. bears N.71½°W., 209 lks. dist.  
A Y.Oak 16" dia. bears N.43°E., 773 lks. dist.

James W. Byron, Deputy County Surveyor - Milo Godfrey; Clete Putnam - January, 1961 - C.S. File 49/50-32

-----  
Found - Orig. 24" now 48" B.Oak N.51½°W., 137.9 ft. We open & find good scribe marks "S".  
Orig. 16" now down 40" Oak N.43°E., 510.2 ft.  
Also find 1" I.P. at corner. E-W fence 15 ft South.  
Brass Cap Not Set.

New BTs - 6" B.O. bears N.29°W., 15.0 ft. scribed ¼ S31 CS BT  
8" W.O. bears N.26°E., 10.7 ft. scribed ¼ S31 CS BT

Doug. County Surveyors Office - Randall Smith, Stephen Flause, May 11, 1993 - C.S. File 64/43-7

-----  
Found - 1" I.D. Iron pipe protruding 4" above ground.  
Source unknown.  
6" now 8" dia. B.Oak with a fully healed double blaze, bears N.29°W., 15.0 ft. (agrees with rec.)  
8" now 11" dia. W.Oak with a fully healed double blaze, bears N.26°E., 10.7 ft. (agrees with rec.)  
24" now 39" dia standing dead oak with a previously opened blaze, scribing visible "S" bears N.71½°W., 137.9 ft.

NE BT is gone  
Set - Referenced position 1" Iron Pipe and set a 2 3/8" x 1¼" O.D. x 32" long iron pipe at referenced position. BC/IP protrudes 8" above ground.  
Brass Cap Marked:

Douglas County Surveyors  
T.27 S.  
¼ S 31 R6W  
T.28 S.  
1993  
Office

1" I.P. measures 20" long is set along south side of BC/IP, protrudes 3" above ground.

New Accessories -  
12" dia W.oak double blazed and scribed "¼ S31 CS BT" bears N.2°E., 45.7 ft. continued next pg

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 131700

PRIMARY CORNER DESCRIPTION South ¼ Cor. for S. 31 only, T27-6

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

6" dia. W.Oak double blazed and scribed "¼ S31 CS BT"  
bears N.52¼°W., 18.7 ft.

Fd. Aug. 1990, M 112-12