TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION No. 1/4 Sec. 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 12 Page 5159)

Set ¼ sec. post, from which
A W.Oak 12" dia., bears S.77°E., 237 lks. dist.
A Y.Oak 24" dia., bears S.8¾°W., 318 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - Jan. 23, 1961 - C.S. 49/50-32

Found - Orig. 12" now 26" W.Oak S.77°E., 156.4 ft. We open and found good scribing "S"
Orig. 24" now 48" B.Oak snag S.8 3/4°W., 209.9 ft. shows scar.
Corner under E.W. fence.
Set brass cap at cor. mkd: County Surveyors Office, 1961
North ¼ S6 T28S R6W
New BTs - 15" W.Oak bears S.73½°E., 42.5 ft. scribed ¼ S6 CS BT.
14" W.Oak bears S.55°W.,35.8 ft. scribed ¼ S6 CS BT

Found OK, August 1990 - M 112-12

Doug. County Surveyors Office - Randall Smith-Stephen Flause. May 13, 1993 - C.S. File 64/43-11

Found - 2½" Brass cap on a 1½" O.D. iron pipe, protruding 18" above ground (1961 Byron)
12" now 26" dia. W.Oak with a previously opened blaze, scribe visible "S", bears S.77°E. 156.4 ft. (Orig. BT)
24" now 48" dia. 12' tall B.Oak snag with a rotted out center and a healed blaze, (note a new 7" dia. B.Oak is growing out of east edge of BT) bears S.8 3/4°W., 211.9 ft.(rec. S.8 3/4°W., 209.9 ft. dist. possible face measurement) Orig. BT.
15" now 23" dia. W.Oak with a fully healed single blaze, bears S.73½°E., 42.5 ft. (1961 Byron)
14" now 20" dia. W.Oak with a fully healed single blaze bears S.55°W., 35.8 ft. (1961 Byron)
New Accessories -
20" dia W.Oak Double blazed and scribed "¼ S6 CS BT bears S.16 3/4°E., 51.7 ft.
Note - Corner lies in an east-west fence line.