

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5732)

Set post, cor. to secs. 29, 30, 31 and 32, from which
A W.Oak 26" dia., bears S.60½°W., 242 lks.
A W.Oak 20" dia., bears N.48°W., 442 lks.
A W.Oak 10" dia., bears S.29½°E., 926 lks.
A W.Oak 18" dia., bears N.86°E., 1440 lks.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; S.A. Bilow - Nov/Dec. 1958 - C.S. File 49/50-25

Found - Orig. 26" now 38" W.Oak S.60½°W., 159.7 ft., I open & find good scribing "31".
Orig. 20" now 40" W.Oak N.48°W., 291.7 ft., shows good scar. I do not open.
I do not look for orig. NE BT.
Orig. SE BT gone.

Set brass cap at cor. mkd: S30|S29 T28S R6W County Surveyors
S31|S32 Office, 1958

(Corner is old rail fence line. See CS file for sketch)

New BTs - 7" double W.Oak S.1°W., 20.2 ft. scribed S31 T28S R6W CS BT.

9" B.Oak S.10½°E., 51.2 ft. scribed S32 T28S R6W CS BT.

15" B.Oak bears N.86°E., 156.0 ft. scribed S29 T28S R6W CS BT.

Fd. BC G. Lang 3/2012 - M163-43

Fd. BC & 3 BTs by Carl Sweeden, 1/2013 - M164-58