

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 17 & 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5738)

Set ¼ sec. post, from which
 A W.Oak 28" dia., bears S.56 3/4°W., 309 lks. dist.
 A W.Oak 13" dia., bears N.85°E., 257 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell - Jan. 1962 - C.S. File 49/139

Found - 8" x 3" x 6" high rock at cor. & both BTs. We open orig. 13" now 25" W.Oak N.85°E., 169.6 ft. & find good scribe.
We chisel a 1" + and 1/4 on top of corner rock.
New BT - 13" W.Oak bears S.58°E., 60.4 ft. scribed ¼ S17CSBT

Doug. County Surveyors Office - Randall Smith; Stephen Flauser April 28, 1988 - C.S. File 62/52-10

Found - Stone, source unknown. The top measures 8" x 3", firmly set and protrudes 6" above ground. Chiseled marks on top per Byron, "+ ¼" found. (A rock was noted as found at corner by W.F. Briggs, County Surveyor in 1893. See Field Book 95 Pg. 22)
28" now 49" W.Oak with a fully healed blaze bears S.56¾°W., 203.9 ft. Orig. BT. (agrees w/rec.)
13" now 28" dia. W.Oak with a previously opened blaze scribing seen "BT" bears N.85°E., 169.6 ft. Orig. BT. (agrees w/rec.)
13" now 18" dia. W.Oak with a fully healed double blaze bears S.58°E., 60.4 ft. (agrees w/rec) 1962 Byron.
Corner stone firmly set and in good shape. No brass cap/iron pipe monument set. We painted corner stone orange.
New BT - 8" W.Oak double blazed & scribed "¼ S18 CS BT" bears N.60½°W., 119.9 ft.

Found OK by M. Heimburger, Jan. 2001 - M132-68