

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5738)

Set post cor. to secs. 7, 8, 17 and 18, from which
A Y.Oak 26" dia., bears N.65°W., 56 lks. dist.
A Y.Oak 36" dia., bears S.47¼°W., 117 lks. dist.
A W.Oak 12" dia., bears S.61°E., 12 lks. dist.
A W.Oak 10" dia., bears N.42½°E., 55 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; S.A. Bilow - Nov. 1958 - C.S. File 49/50-29

Found - Orig. 26" now 40" rotted stump N.65°W., 37.0 ft., good scribing "BT".
Orig. 10" now 30" W.Oak N.42½°E., 36.3 ft., checks bearing and distance.
Orig. 12" now 30" W.Oak shows old scar. I do not open, S.61°E., 8.0 ft.
No trace of original SW BT.
Set brass cap at cor. mkd. S7|S8 T28S R6W County Surveyor's S18|S17 Office, 1958
New BTs - 10" W.Oak bears S.61½°W., 71.5 ft. scribed S18 T28S R6W CS BT.
12" W.Oak bears N.63½°W., 11.9 ft. scribed S7 T28S R6W CS BT.
See sketch in file for location of this corner.