

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5740)

Set post cor. to secs. 5, 6, 7 and 8, from which
A Y.Oak 18" dia., bears S.18°W., 475 lks.
A Y.Oak 18" dia., bears S.37°E., 230 lks.
A Y.Oak 15" dia., bears N.57 3/4°E., 614 lks.
No tree near in sec. 6.

A. Boyer, D.C.S -Wit: Clyde Heater; Ralph Heater -Aug 15, 1942
- C.S. File 36/48; Vol. 4 Pg. 95; "old" cor. book, Pg. 182

Position identified from OBTs in SW and SE quadrants.
OBT in NE quadrant gone. Set a 18" x 6" rock for corner and marked 2 new trees:
12" W.Oak S.48½°E., 93.5 ft.
8" W.Oak N.69½°E., 202 ft.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; S.A. Bilow - May 21, 1958 - C.S. File 49/73-4

Found - Both BTs as renewed by Boyer, check for bearing and distance, show good faces, I do not open.
Boyer's rock at corner and a 1" steel shaft at cor.
Set brass cap at cor. alongside rock and shaft marked:
S6|S5 T28S R6W County Surveyors Office, 1958
S7|S8
Blazed and scribed 6" B.Oak S.0°30'W., 12.9 ft. S7 T28S R6W CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 11/12/2002 - C.S. File 66/48-5

Found - 1958 DCSO brass cap iron pipe, protrudes 14" out of ground. 1" steel shaft along N'ly edge of BC/IP 13" out of ground. No stone visible. Corner is 1 ft. south of a NE'ly fence line.
12" now 21" dia., W.Oak with a fully healed blaze, bears S.48½°E., 94.5 ft. (rec. S.48½°E., 93.5 ft.) (1942)
8" now 17" dia., W.Oak with fence line grown into trunk bears N.69½°E., 202.0 ft. (1942)
6" now 18" dia., B.Oak with a fully healed double blaze bears S.0½°W., 12.9 ft. (1958)
No evidence of orig. SE BT fd., orig. NE BT noted as NF in 1942.

continued next page

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

New -	18" now 32" dia., down Oak not tied (rec. S.18°W., 313.5 ft.) OBT? 8" dia., W.Oak double blazed & scribed "T28S R6W S6 CS BT" bears N.74½°W., 64.8 ft. Compass decl. 17½°E.