

PRIMARY CORNER DESCRIPTION Cor. for secs 5 & 6 (N) only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Original - Elder & Gile, Contract #31 dated April, 1853 ----- Set post cor. to Secs. 5 and 6, from which A W.Oak 12" dia. bears S.61°W., 1030 lks. Made trench, no tree near. E. Saxton's house, bears N.11¼°W.</p>
<p>Douglas Co. Surveyors Office - James W. Byron; Milo Godfrey Clete Putnam - Jan. 23, 1961 - C.S. File 49/50-33 ----- Found - Orig. 12" now 24" W.Oak S.61°W., 679.8 ft. We open & find good scribing "S8". Set - Brass cap at corner mkd. County Surveyor's Office 1961 T28S R6W S 6 S 5 New BTs- 24" B.Oak bears S.88°W., 497.0 ft. scribed S6 T28S R6W CS BT. No tree near to S.E. S.E. corner of stock barn bears N.60°W., 121.5 ft.</p>
<p>Doug. Co. Surveyors Off. - John Powell, W. Penley, December, 1970 - C.S. File 49/50-61 ----- Found - 1961 DCS0 brass cap, properly mkd., but disturbed from original position. Orig. 24" W.Oak, S.61°W., 679.8 ft., tree opened before, scribe visible "S" & other marks. 24" B.Oak S.88°W., 497.0 ft. tree partially grown over, parts of scribing visible. Set - New brass cap at cor. with steel post alongside & old brass cap in hole, set in concrete mkd. County Surveyors T27S S 32 Office, 1970 T28S S 6 S 5 R6W New BT - 24" B.Oak N.20°W., 534.3 ft. scribed T27S R6W S CSBT Set - 5/8" I.R. N.20°W., 29.1 ft. in E-W fence line. Note - Brass cap 7" underground.</p>
<p>Doug. County Surveyors Office - Randall Smith, Stephen Flause May 24, 1993 - C.S. File 64/43-29 ----- Found - 2½" dia. DCS0 brass cap set in concrete is found 7" below ground. Broken off metal fence post is found 6" east of brass cap 7" below ground. 12" now 2 ft. high burnt double trunked oak with reverse scribing "BT" found on 18" southerly trunk. Center of roots bears S.61°W., 679.8 ft. Orig. BT. continued next page</p>

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Cor. for secs 5 & 6 (N) only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

24" now 31" dia. B.Oak with a fully healed double blaze, bears S.88°W., 497.0 ft. (1961 Byron)
24" now 28" dia. B.Oak with a fully healed double blaze bears N.20°W., 534.3 ft. (1970 Powell)
5/8" Iron rod bears N.20°W., 29.1 ft. (1970 Powell)
New Accessories -
18" dia. B.Oak double blazed and scribed "T28S R6W S6 CS BT", bears S.82°W., 508.0 ft.

Found OK by K. DeGroot, July 2000 - M135-20

DCS0-GIS Corner visitation - 7/13/2004 - Typed: 1/31/2011 - C.S. File 67/33-1

Monument - BC/IP 1.25"
Comment - ok