

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 5 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5740)

Set 1/4 sec. post, from which
 A Y.Oak 7" dia., bears N.20°E., 55 lks.
 A Y.Oak 20" dia., bears S.50 1/2°E., 80 lks.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; S. Bilow - March 31, 1958 - C.S. File 49/73-2

Found - Orig. 7" now 18" B.Oak N.20°E., 36.3 ft. This BT recently opened, good scribing visible "1/4 S".
 I do not find original SE BT.
Set brass cap at cor. mkd: 1/4 S5 T28S R6W County Surveyor's
 S8 Office, 1958
Corner at wire fence corner.
New BTs - 13" R.Fir bears S.7°W., 26.4 ft. scribed 1/4 S8 CSBT
 6" W.Oak bears N.29°W., 11.6 ft. scribed 1/4 S5 CSBT

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 11/13/2002 - C.S. File 66/48-7A&B

Found - 1958 DCSO brass cap iron pipe at fence corner. Fence lines run N+E. Protrudes 13" out of ground.
 Orig. NE BT now gone
 13" now 24" dia., 2 ft. high D.Fir stump with a healed lower blaze, bears S.7°W. 26.4 ft (1958)
 6" now 10" dia., W.Oak with a fully healed double blaze bears N.27°W., 11.6 ft. (rec. N.29°W., 11.6 ft.) (1958)
New - 12" dia., I.Cedar double blazed & scribed "1/4 S8 CS BT" bears S.51°W., 54.3 ft.
 16" dia., B.Oak double blazed & scribed "1/4 S5 CS BT" bears N.54°E., 21.8 ft.
 18" dia., Madrone double blazed & scribed "1/4 S8 CS BT" bears S.11 1/2°E., 47.5 ft.
 Compass decl. 17 1/2°E

Following positions are for location purposes only
NOT SURVEY GRADE

Equipment: Trimble GEOEXPLORER 3 System
File: R111420A
Point Names: T28SR6W SQ5

	<u>1927</u>		<u>1983</u>
OCS	N 556625	E 1217574	N E
Latitude:	43°09'23.1"		Latitude:
Longitude:	123°25'58.8"		Longitude:
Offset to corner?	Yes		Corrected for? Yes _____