

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 16 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Pages 5728-29)

Set ¼ sec. post, from which
 A Y.Oak 10" dia., bears S.46°E., 277 lks. dist.
 A Y.Oak 8" dia., bears S.82½°W., 57 lks. dist.

F.C. Frear, For Adair - Jan. 1918 - Field Book 44 Pg. 20-22 & "old" cor. book, Pg. 182

Found Y.Oak S.48°E., 2.77 chs. and Y.Oak S.80°W., .57 chs.
Corner is a large boulder. Marked BT:
 B.Oak 24" dia., bears N.78°W., 46 lks.

Doug. County Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell - Jan. 1962 - C.S. File 49/139-26

Found - Pointed rock at corner 6" above ground.
 Now (?) B.Oak N.78°W., 30.4 ft. shows good scars, recorded by Frear.
 Fence corner thus: x ↑
 |
 --x--●--x--x
Set brass cap alongside cor. stone & mkd. County Surveyors Office 1962 ¼ S17|S16 T28S R6W
New BT - 5" W.Oak bears N.5½°E., 13.0 ft. scribed ¼ S16 CSBT.

Found OK, Glenn Baughman, Feb. 1988, M 105-55
Found OK, Janet Lundeen, Sept. 1997, 1997-0099A&B
Fd. Ok by Raymond Brown, May 2004-Sept. 2008 - RM 4-16