

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. cor. for 8, 9, 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5729)

Set post cor. to secs. 8, 9, 16 and 17, from which
A Y.Oak 10" dia., bears N.40°E., 17 lks. dist.
A Y.Oak 14" dia., bears S.35°E., 37 lks. dist.
A W.Oak 8" dia., bears S.39°W., 42 lks. dist.
A W.Oak 10" dia., bears N.87°W., 55 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell - Jan. 1962 - C.S. File 49/139-23 (See also C.S. File 44/120)

Found - Orig. 8" now 12" W.Oak S.39°W., 27.7 ft., previously opened, shows good scribing "BT".
Orig. 10" now 20" W.Oak N.87°W., 36.3 ft. shows scars.
Found stump hole for SE BT.
NE BT not found.
Set brass cap at cor. mkd: County Surveyors S8|S 9 T28S R6W
Office 1962 S17|S16
New BTs - 5" W.Oak bears S.42°E., scribed S16 T28S R6W CSBT.
Rescribe O.B.T., now 20" W.Oak N.87°W., 36.3 ft.
S8 T28S R6W CS BT. (Upper scribing on NE face.
No trees near to NE.
Corner is at 4 way fence corner.

Doug. County Surveyors Office - Randall Smith; Stephen Flauser April 25, 1988 - C.S. File 62/52-8

Found - A 1½" O.D. I.P. with a 2½" dia. 1962 DCSO brass cap protruding 18" above ground. Top of BC/IP is leaning 10" North of a plumb position.
8" now 11" dia. W.Oak with a fully healed double blaze bears S.39°W., 27.7 ft. (agrees w/rec.)
Orig. BT.
Orig. 10" now 24" dia. W.Oak with a partially healed blaze, no scribing visible, bears West, 37.4 ft. (Rec. N.87°W., 36.3 ft.)
5" now 9" dia., W.Oak with a fully healed double blaze bears S.44°E., 18.5 ft. (Rec. S.42°E., no distance shown in Ren. record from 1962, BT tag shows dist. as 18.5 ft. which we agree with)

(Cont. Next Page)

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set - plumb position of DCS0 BC/IP is referenced and mounument removed. DCS0 BC/IP is a 36" long split end I.P. which is reset at referenced plumb position & now protrudes 8" above ground.
New BT - 5" Madrone bark scribed "T28S R6W S9 CS BT" bears N.42°E., 40.1 ft.
Corner is located Southeast of Wildlife Safari picnic area, 3 ft. South of a trail where remnants of old woven wire fences were seen running East, West and South.

Fd. Ok by Raymond Brown, May 2004-Sept. 2008 - RM 4-16