TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5730)

Set ¼ sec. post, from which
A Y.Oak 10" dia., bears S.47°E., 78 lks. dist.
A Y.Oak 14" dia., bears N.48°W., 11 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell - Jan. 1962 - C.S. File 49/139-24

Found - Orig. 10" now 28" B.Oak S.47°E., 51.5 ft. We open & find good scribe marks.
Orig. 14" now 30" B.Oak N.48°W., 7.3 ft. shows scar.
Fence corner thus:--x-●-x--
|
Set brass cap at cor. mkd: County Surveyors Office, 1962
↑
¼ S8|S9 T28S R6W
New BTs - 32" B.Oak bears S.73°E., 88.6 ft. scribed ¼ S9 CSBT
10" W.Oak bears N.80°W., 25.5 ft. scribed ¼ S8 CSBT

Fd. Ok by Raymond Brown, May 2004-Sept. 2008 - RM 4-16