

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Pages 5730-31)

Set post cor. to secs. 4, 5, 8 and 9, from which
A W.Oak 18" dia., bears S.34°W., 171 lks. dist.
A Y.Oak 10" dia., bears S.3¼°E., 170 lks. dist.
A Y.Oak 20" dia., bears N.53°E., 346 lks. dist.
A W.Oak 10" dia., bears N.52½°W., 346 lks. dist.

H.L. Eppstein, Deputy Co. Surveyor - For: Geo. Telford - Jan. 9, 1920 - Field Book 44 Page 40; C.S. File 5/9; "old" cor. book, page 108.

Reset from old BTs by setting a 3/4" x 30" Iron pipe, from which:
A W.Oak 14" dia., bears N.48°W., 115 lks.
A B.Oak 14" dia., bears S.45°E., 147½ lks.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; S.A. Bilow - May 21, 1958 - C.S. File 49/73-3

Found - 3/4" I.P. at sec. cor. & 4-way fence corner.
14" now 28" W.Oak N.48°W., 75.9 ft., I open and find good scribing.
The SE BT gone.
I reblaze and rescribe 28" W.Oak N.48°W., 75.9 ft. "S5 T28S R6W CS BT".
Blaze and Scribe:
20" B.Oak N.45°E., 1.8 ft. "S4 T28S R6W CS BT".
8" B.Oak S.25½°E., 105.2 ft. "S9 T28S R6W CS BT".

Found OK by R.Ware, May 1984 - M 96-71

Doug. County Surveyors Office - Randall Smith; Stephen Flauser March 16, 1990 - C.S. File 64/6-10

Found - 3/4" O.D. I.Pipe with an unmarked 1½" dia. I. Cap on top, 8" below ground.
14" now 36" dia. 1 ft. high Oak stump, no blazes or scribing visible, bears N.48°W., 75.0 ft. (Rec. 75.9 ft. possible slope measurement)

(Cont. Next Page)

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

8" B.Oak now depression in ground bears S.25½°E.,
105.2 ft. (agrees w/record) (1958)
20" now 31" dia. B.Oak with a fully healed double
blaze, bears N.45°E., 1.8 ft. (agrees w/record)
No other original or renewal bearing trees are
found.
New BTs - 9" dia. Ash double blazed and scribed "T28S R6W S8
CS BT" bears S.54 3/4°W., 136.8 ft.
12" dia. W.Oak double blazed & scribed "T28S R6W S9
CS BT" bears S.9°E., 145.8 ft.
28" dia. W.Oak double blazed & scribed "T28S R6W S5
CS BT" bears N.19½°W., 93.0 ft.

Fd. Ok by Raymond Brown, May 2004-Sept. 2008 - RM 4-16

DCS0-GIS Corner visitation - 7/14/2004 - Typed: 2/1/2011 -
C.S. File 67/33-1

Monument - Buried Iron pipe
Comment - OK