TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5725)

Set ¼ sec. post, from which
A W.Oak 20" dia., bears N.60°E., 38 lks. dist.
A W.Oak 18" dia., bears S.35°E., 31 lks. dist.

Jesse W. Cole, Deputy for: Round Prairie Ranch - Dec. 1920 "old" corner book, page 109; Field Book 49 Page 61; Vol. 3 Page 83

Renew corner from remains of old bearing trees which are down but check for direction and distance.
Set 1/2" x 30" Iron pipe, also post, from which:
A Laurel 40" dia., bears S.89°W., 37.5 ft.
An Oak 10" dia., bears S.38°E., 44.0 ft.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - Dec. 1961 - C.S. File 49/139-14

Found - Stump shell that fits orig. NE BT and impression in ground that fits SE BT. Chopped open and found scribing "¼S" on 40" Laurel, set by Cole, 1921.
Did not find 1/2" I.Pipe.
10" Oak scribed by Cole showing good scars to be an 18" W.Oak bearing S.29°E., 45.0 ft.
40" Laurel fits original BT remains. Also is alive & standing.
Set brass cap at fence cor. mkd: Co. Surveyors ¼ $\frac{S28}{S33}$ T28S R6W Office, 1961
Fence running N, S, & W.
New BT - 8" W.Oak N.10½°E., 21.8 ft. scribed ¼ S28 CS BT.

Howard Johnstone -For: Roseburg Forest Products - F.White; F. Raddatz; B.Olson; - Oct. 15, 1986 - C.S. File 63/26-4

Found - Brass cap/iron pipe.
40" Laurel S.89°W., 37.5 ft. down and rotted.
8" Oak N.10½°E., 21.8 ft. healed face.
No sign of Oak S.29°E., 45.0 ft. - in meadow.
New BT - 9" Oak S.40°W., 33.5 ft. face, scribed & tagged.

Found OK by D. Beedle, June 2000 - M135-24