TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 9 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Pg. 5730)

Set ¼ sec. post, from which
An Ash 20" dia., bears S.18½°W., 92 lks. dist.
A W.Oak 11" dia., bears N.50½°W., 192 lks. dist.

Geo. Wenderoth - May 1951 - C.S. File 44/120

Set 1" I.Pipe half way between section corners, from which
12" W.Oak S.77°20'W., 122.9 ft.
36" B.Oak S.39°10'W., 233.1 ft.
Did not find Iron pipe.

H.L. Northcraft - Feb. 1971 - M 41-24

Set 5/8" x 36" Iron rod at corner.

Bruce Shaner Engineering - July 23, 1979 - C.S. File 58/176-14

Set brass cap mkd. "T28S R6W W.M. 1/4 S9, S16 P.L.S. 430 1979"
From which:
18" W.Oak BT mkd. by Wenderoth bears S.77°20'W., 122.9 ft
36" B.Oak BT mkd. by Wenderoth bears S.39°10'W., 233.1 ft

FD OK by B.Shaner, May 1995 - M 122-10
Fd. Ok by Raymond Brown, May 2004-Sept. 2008 - RM 4-16