

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 371700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33-34; T27-6 only (south)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

.... Briggs calls a 20" Ash, N.76½°E., 300 lks. (198.0') matching orig. record to a 14" Ash. Byron found scribing in this tree during his visit.

A 54" now 58" dia. W.Oak with well healed single blaze 5½ ft. above ground on a westerly trunk bears S.63°E., 307.5 ft.

Byron's sketch shows an anchor post N.54°E., at 31 ft. We find a gate post bearing N.54°E., 33.0 ft. This is probably not the same post tied by Byron, portions of this fence have been rebuilt.

Set - A 1" x 30" Iron pipe with attached brass cap 42" deep (cap is 14" below surface) at the corner position. Cap mkd. "Douglas County Surveyor T27S R6W CC S33 S34 1984".

New - A 6" W.Oak double blazed & scribed "CC T27S R6W S33 CS BT" bears N.72°W., 360.9 ft.

5/8" x 30" iron rod with "Douglas Co. Surveyor" alum. cap attached & stamped "B0 1", set in fence line (running S.56°E.) 4" above ground bears N.86¼°E., 52.0 ft.

5/8" x 30" iron rod with "Douglas Co. Surveyor" alum cap attached & stamped "B0 2" set in fence line (running S.56°E) 4" above ground bears N.4¼°W., 38.1 ft.

Note: sketch in C.S. File. Corner falls in dim track road.

Fd. Ok by Raymond Brown, May 2004-Sept. 2008 - RM 4-16