

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5717)

Set ¼ sec. post, from which
 A Fir 36" dia., bears N.80°W., 18 lks. dist.
 A Fir 40" dia., bears N.7°E., 43 lks. dist.

Jesse Cole; for:Round Prairie Ranch - Dec. 1920 - Vol. 3 Page 83; Field Book 49 Page 57; "old" cor. book, Pg. 109

Orig. BT, N.7°E., standing and alive. Stub of orig. BT, N.80°W., standing but dead, scribe marks visible, distance and direction check by using slope measure to tree N.7°E.
Set 4" x 4" x 40" Oak stake and erected mound of rock.

Doug. County Surveyors Office - N.E. Richardson; M.E. Godfrey L.S. Kershner, wit. - Mar. 1947 - C.S. File 39/70; M 25-20

Found - O.B.T. N.7°E., 43 lks. slope dist. and stump of other. Also found mound of rock.
Set a 1" x 36" Galv. I.P. with a brass cap stamped: "County Surveyors Office S27|S28, from which
 12" Fir bears N.66½°W., 16.5 ft. mkd. CS BT S28
 20" Fir bears S.51 ¾°E., 13.3 ft. mkd. CS BT S27.

Doug. County Surveyors Office - Vernon Tracy; Jack Heritage; E. West - Sept 1, 1967 - C.S. File 49/139-116

Found - 1947 DCSO brass cap & BTs as recorded by Richardson. Original bearing tree alive.
Richardson's BTs are now snag to NW and stump to SE with scribe visible.
Set 6 ft. steel fence post 2.0 ft. north of corner.
New BTs - 11" Laurel N.3°E., 9.5 ft. mkd. ¼ S27 CS BT.
 13" Laurel S.23°W., 41.4 ft. mkd. ¼ S28 CS BT.
This corner lies on steep north slope approx. 350 ft. south of S.P. RR, course E. and W.

Fd. Ok by D.Bentz, 7/97 - 1997-0138
Found OK by D. Beedle, June 2000 - M135-24
Fd. Ok by G. Lang - 4/2007 - M153-20