

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. cor. for 9, 10, 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5721)</p> <p>-----</p> <p>Set post at foot of hill, cor. to secs. 9, 10, 15 and 16, from which</p> <p>    The top of a conical rock of 4 ft. base, about 3 ft. high, bears N.12½°E., 109 lks.</p> <p>    A ledge of rocks bears East of it about 100 lks.)</p> <p>Drove charred stake and raised mound with trench etc, as per instructions.</p>
<p>Don E. Garrett, for: McLaughlin - August 1970 - M 40-25</p> <p>-----</p> <p>Found - Stone for Wenderoth corner. (See C.S. File 44/120)</p> <p>Replaced with 5/8" Iron rod.</p> <p>Face of large rock bears N.12°30'E., 71.94 ft. and East, 47 ft. measured on slope.</p>
<p>Found cor. &amp; a "post", Glenn Baughman, Feb, 1988, M 105-55</p> <p>Fd. Ok by Raymond Brown, May 2004-Sept. 2008 - RM 4-16</p>
<p>Fd. 5/8" IR by M. Heimbürger, 11/2013 - C.S. File 65/79-19</p>