

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 34; & 3 of T29-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5700)

Set 1/4 sec. post, from which
 A W.Oak 14" dia., bears N.26°E., 142 lks. dist.
 A W.Oak 15" dia., bears S.47°E., 115 lks. dist.
Robert Phipps house bears S.59°W., 4 chs. dist.

Jesse Cole, Deputy - Wit: L.H. Smick; Glen Taylor - Dec. 1920-
Jan. 1921 - Vol. 3 Page 84; "old" corner book, Page 109

Renewed corner from orig. BT, S.47°E., 75.9 ft. which is alive
and standing. Scar had been chopped out but old blaze had
rotted no scribe marks visible.
Found hold where tree had stood N.26°E.
Remains of fire place of Robert Phipps cabin bears S.59°W.
Mark new tree N.56°E., 82.1 ft. (B.Oak)
Set an Oak post, 4 x 4 x 40", also an Iron Bolt 5/8" x 24".

Doug. County Surveyors Office - James Byron, Deputy - Dale
McFarland; John Powell - Dec. 1961 - C.S. File 49/139-4

Found - Orig. 15" now down, large Oak S.47°E., 76.0 ft. We
find good reverse scribing on old section near
base "1/4S.
Now 36" B.Oak N.56°E., 82.1 ft. shows good scars,
recorded by Cole.
Find 5/8" Bolt at corner.
Set B.C. alongside bolt & mkd: County Surveyors 1/4 S34 T28SR6W
Office, 1961 S 3 T29S
New BTs - 6" W.Oak bears S.35°E., 18.2 ft. scribed 1/4 S3 CS BT.
14" W.Oak bears N.3 1/2°E., 42.2 ft. scribed 1/4 S34 CSBT

Fd. ok H. Pieske, Oct. 86, M 102-53.

DCSO-GIS Corner visitation - 7/15/2004 - Typed: 2/1/2011 -
C.S. File 67/33-1

Monument - BC/IP - 1.25"
Comment - OK

Fd. ok by R. Brown, 6/2006-10/2007 - RM 4-15A&B