TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Pages 5721-22)

Set ¼ sec. post, from which
The East point of a rock, 3 ft. x 6 ft. base, and 3 ft. high, bears S.73¼°W., 296 lks. dist.
The NE cor. of a rock, 15 ft. x 20 ft. base, and 10 ft. high bears N.88¼°W., 618 lks. dist. This is the North one of several rocks extending south of it 4 or 5 chs.
Made trench as per instructions.

Doug. County Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell - Jan/Feb. 1962 - C.S. File 49/139-28

Found - Both rocks as recorded in original survey.
12" x 6" x 24" stone, 6" out of ground at four-way fence corner & at true corner.
Set brass cap alongside west edge of corner stone and marked:
County Surveyor's Office, 1962 ¼ S10/S15 T28S R6W
No trees near for bearing trees.

Found BC, July 1985, Eugene Bloom, M 99-3
Fd. BC, R. Dolan, July 1987, M 104-52
Found OK, Dec. 1990, D. Bentz, Partition 1991-0001
Fd. BC in 4-way fence corner, no BTs. Dec. 1991, D. Bentz, Partition 1992-0008
Found ok, March 1994, D. Bentz, Partition 1994-0047
Found OK, July 1996, K. DeGroot, Partition 1996-0063
Fd. BC by R. Quimby, 3/2007 - 2007-0051