TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Pages 5710-11)

Set post cor. to secs. 22, 23, 26, and 27, from which
A Y.oak 14" dia., bears S.55°E., 65 lks. dist.
A W.Oak 6" dia., bears N.68°E., 38 lks. dist.
A Y.Oak 12" dia., bears N.23°W., 22 lks. dist.
A Y.oak 10" dia., bears S.2°W., 51 lks. dist.

J.W. Cole, for: Round Prairie Ranch - Dec. 1920 - Vol. 3 Page 83 - Field Books, 49 and 50

Cor. was marked by an old stake setting at the fence cor. and witness trees were standing and alive. I renewed the corner by setting a post 4" x 4" x 40", also an iron pipe ½" x 30"

Doug. County Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell - Dec. 1961 - C.S. 49/139-9

Found - Orig. 6" now 12" W.Oak N.68°E., 25.1 ft. We open and find good scribing "R6".
Orig. 10" now 20" B.Oak S.2°W., 34.6 ft. not 36.7 ft. We do not open.
Orig. 12" now 20" B.Oak N.23°W., 14.5 ft. shows old face, now rotted.
Orig. SE BT not found
Find gun barrel at corner.

Set brass cap mkd: County Surveyors Office, 1961

S22	S23
S27	S26

T28S R6W

New BTs - R.Fir bears N.28½°E., scribed S23 CS BT.
Rescribe orig. now 20" B.Oak N.23°W., 14.5 ft. mkd. T28S R6W S22 CS BT.
13" R.Fir bears S.21°E., 46.8 ft. scribed S26 T28S R6W CS BT.

Fences thus:



Fd. ok by R. Brown, 6/2006-10/2007 - RM 4-15A&B