

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5713)

Set ¼ sec. post, from which
 A Y.Oak 18" dia., bears S.78½°W., 199 lks.
 A Y.Oak 14" dia., bears N.55½°W., 300 lks.
 No tree East of line.

Doug. County Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell - Jan. 15, 1962 - C.S. File 49/139-21

Found - Orig. 18" now 44" B.Oak S.78¼°W., 131.3 ft., shows good scars.
 Orig. 14" now 40" B.Oak stump N.55½°W., 198.0 ft.
 We open & find good scribing "B".
Set Brass cap at South side of anchor post mkd: County Surveyors Office 1962 ¼ S15|S14 T28S R6W
(Cor. at intersection of N-S and E-W fences.)
New BTs - Rescribed O.B.T., now 44" B.Oak S.78½°W., 131.3 ft.
 ¼ S15 Cs BT"
 11" Laurel N.47½°W., 159.8 ft. scribed ¼ S15 CS BT.
 No trees near East of section line.

Fd. OK, James Artman, Feb. 1992, Partition 1992-0020
Fd. Ok, D. Bentz, July 1995, M 122-57
Fd. Ok, K. DeGroot, April 1998 - 1998-130 A&B

Douglas Co. Surveyor's Office - Crew: Jeff Lorsung - 7/24/2025 - C.S. File 67/61-4

Found - DCSO brass cap (properly mkd)
 38"x3 ft. Oak stump S.78¼°W., 131.3 ft., shows good scar.
 42" B.Oak stump N.55½°W., 198.0 ft.
 24" Laurel N.47½°W., 159.8 ft.
 5/8" iron rod with cap marked BTS N.45°E., 19.0 ft.
 BTs not spiked due to distance and slope.
New - 4"x8' metal post with solar panel S.87°E., 7.9 ft.
 Wood lath 6" South.
Note - Compass decl. 14¼°E.
 Corner is 12 ft west of N-S & E-W fence intersection
O CRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
43°08'03.93151" N 123°23'05.05055" W