

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 531700

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 35, T27-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
 A W.Oak, 18" dia. bears N.43 ¾°E., 996 lks. dist.
 A W.Oak, 22" dia. bears N.14¼°W., 1242 lks. dist.

James W. Byron, Deputy - Milo Godfrey; Clete Putnam
January, 1961 - C.S. File 49/79-21

Found - Remains of 2 old Oaks that check record distance
 & bearing. Each shows pieces of old windows
 & axe work. No scribing found.

No evidence of any old Oaks that would be closer
to corner. The location of cor. checks by
compass & pacing from known corner.

Set - Brass cap at corner mkd. County Surveyor's Office
 1961, South ¼ S35 T27S R6W

New BTs - 6" Ash bears S.49°W., 122.0 ft. scribed S¼ S35 CSBT
 8" W.Oak, N.12°W., 479.8 ft. scribed ¼ S35 CS BT.
 6" W.Oak, N.3½°E., 330.6 ft. scribed ¼ S35 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Stephen J.
Flause; June 22, 1993 - C.S. File 64/46-6

Found -
 2½" Brass Cap on a 1¼" O.D. iron pipe, leans 1 ft. south
 of plumb protruding 14" above ground. (1961 DCS0 BC)
 18" now down and rotted Oak, old axe mark found, root
 hole bears, N.44 ¾°E., 653.7 ft. (rec. N.43 ¾°E.
 657.4 ft.)

 22" now down with scattered Oak remains found near record
 bearing & distance (N14¼°W., 819.7 ft.) Orig. BT

 8" now 11" dia. W.Oak, with a fully healed double blaze,
 bears N.12 ¾°W., 480.8 ft. (rec. N.12°W., 479.8
 ft.) 1961 BT

 6" now 11" dia. W.Oak, with a fully healed invisible
 blaze, I opened and find illegible scribe marks,
 bears N.2 ¾°E., 332.2 ft. (rec. N 3½°E., 330.6')

 SW Ash from 1961 renewal now gone.

Note - BC/IP returned to plumb position, protrudes 14" above
ground by a loose mound of stones.

New Accessories -

 18" B.Oak, double blazed and scribed "¼ S35 CS BT" bears
 N.63½°E., 433.4 ft. (Cont. Next Page)

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 531700

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 35, T27-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New Accessories continued -
23" W.Oak, double blazed and scribed "¼ S35 CS BT" bears
N.40½°W., 559.7 ft.
Note - Corner lies 3 ft. north of most northerly sewer ponds
north fence line.

Fd. Ok by Raymond Brown, May 2004-Sept. 2008 - RM 4-16