

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5712)

Set ¼ sec. post, from which
A Y.Oak 20" dia., bears N.58½°E., 145 lks. dist.
A Y.Oak 14" dia., bears S.67°W., 409 lks. dist.

Frank Cain; Chas. Schuanfar - Sept. 12-13, 1901 - Vol. 2 Page 264 and Vol. 2 Page 112

The original BT destroyed by being cut down.
Set W.Oak post 4 x 4" sq. 3½ ft. long, from which
B.Oak 8" dia., bears N.49½°W., 371 lks.
B.Oak 5" dia., bears S.23°E., 20 lks.

Doug. County Surveyors Office - James Byron; Dale McFarland; John Powell - Jan. 1962 - C.S. File 49/139-19

Found - 8" now 24" B.Oak stump N.49½°W., 244.9 ft., shows good reverse scribing "S 1".

SE BT not found.
No original BTs found.

Set brass cap at cor. mkd: County Surveyors ¼ S14 T28S R6W Office, 1962 S23

New BTs - 12" W.Oak bears N.39½°W. 54.0 ft scribed ¼ S14 CS BT
17" Double W.Oak S.82°W. 27.9 ft scribed ¼ S23 CS BT
(See sketch in CS file for relationship to fences.)

Fd Brass Cap by Robert Dolan, Feb. 1994 - M 118-29
Fd. BC & BTs of rec. by N. Hibbs, 1/2007 2007-0013