

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5702)

Set ¼ sec. post, from which
 A Y.Oak 12" dia., bears N.62°E., 59 lks.
 A W.Oak 18" dia., bears N.14°W., 53 lks.

W.H. Woods, Wit: W.S. Crear - Nov. 8, 1925 For: S.E. Moore
C.S. File 3/21; M 5074; Vol. 3 Pg. 228 and "old" cor. book,
Page 109

Set from old BT. One tree rotting but identified, other BT
down. Set Oak stake 3x3x20 scribed ¼ S 34 35 CS, from which
 B.Oak 12" dia., bears N.40°15'W., 89 lks. scribed BT S35
 CS.
 B.Oak 12" dia., bears N.54°45'E., 82 lks. scribed
 B.T. S.36 C.S.

Doug. County Surveyors Office - James Byron, Deputy - Dale
McFarland; John Powell - Dec. 1961 - C.S. File 49/139-6

Found - Both BTs recorded by Woods, 1925.
 12" now 18" B.Oak N.56½°E., 54.1 ft. shows good scar
 12" now 16" B.Oak stump N.40°15'W., 58.7 ft. shows
 good scribing "B".
 1" x 18" I.Pipe at corner, not of record.
Set brass cap alongside I.P. & mkd: County Surveyors Office
1961 ¼ S35|S36 T28S R6W
New BT - 22" B.Oak bears N.25°W., 93.5 scribed ¼S35 CSBT

Doug. County Surveyors Office - Gregory Quibell, Deputy -
John Powell - August 4, 1982 - C.S. File 62/1-4

Found - 1961 DCSO brass cap with 1" I.P. alongside
 protruding 14" out of ground. Cap properly
 marked.
Search for BTs revealed no evidence left from either 1925 or
1961.
New Accessories:
 8" W.Oak scribed "¼ S36 CS BT" in double blaze bears
 N.50½°E., 82.4 ft. (Cont. Next Page)

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

8" W.Oak scribed "¼ S36 CSBT" in double blaze bears
N.69°E., 75.0 ft.
18" B.Oak scribed "¼ S36 CS BT" in double blaze bears
S.2°E., 36.8 ft.
SE corner new metal barn bears N.73½°W., 67.5 ft.
Fence corner with fences running North, South, and West
bears S.57°E., 121.7 ft.
(Sketch in C.S. File)

Found N.69°E. and S.2°E., BTs OK, Don Branch, Sept. 1992,
M 112 - 56

Greg Lang - For: Umpqua Lumber Co. - Dec. 2004 - M147-12

Set -5/8" x 30" iron rod (MKD: LANG SURVEYING) from existing
bearing trees:
21" Oak bears S.3°E., 36.8' (36 8')
13" Oak bears N.69°E., 75.0' (75.0')
12.5" Oak bears N.50½°E., 82.5' (82.4')
Fc. Post bears S.56½°E., 121.6' (121 .7')
Note-The barn has been enlarged & no longer fits the call
given in 1982 to its SE corner.

Fd. ok by R. Brown, 6/2006-10/2007 - RM 4-15A&B