

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5704)

Set post cor. to secs. 23, 24, 25 and 26, from which
A Y.Oak 30" dia., bears N.58½°W., 83 lks. dist.
A Y.Oak 32" dia., bears N.58½°W., 83 lks. dist.
A Y.Oak 14" dia., bears S.48½°E., 170 lks. dist.
A Y.Oak 24" dia., bears N.60°E., 255 lks. dist.

Jesse Cole - December 1920 - Vol. 3 Pg. 83; Field Book 49 Page 45

Renewed from two orig. BTs which bear as follows:
An Oak 30" dia., bears N.60°30'E., 168.3 ft. old scribe.
An Oak 30" dia., bears S.48°30'E., 112.2 ft. bears old scribe.
Set Oak stake 4 x 4 x 40".
Marked new trees as follows:
An Oak 6" dia., bears S.19°W., 16.5 ft.
An Oak 38" dia., bears N.31°30'W., 56.4 ft. This tree shows scar but could not be identified as an orig. BT on account of rot.

Doug. County Surveyors Office - James W. byBon, Deputy - Dale McFarland; John Powell - Dec. 1961 - C.S. File 49/139-10

Found - 6" now 18" W.Oak S.19°W., 16.5 ft. shows good scribe marks "S"
Orig. 30" now 38" B.Oak snag N.31½°W., 56.4 ft.
Orig. 14" now down & rotted Oak S.48½°E., 112.0 ft.
Orig. 24" now 36" B.Oak N.60½°E., 168.3 ft. shows good scar.
Ser brass cap mkd: County Surveyor's S 23 | S 24 T28S R6W
Office, 1961 S 26 | S 25
New BTs - 11" Laurel bears N.48°E., 46.0 ft. scribed S24 T28S R6W CS BT.
8" W.Oak bears N.54°W., 32.0 ft. scribed S23 T28S R6W CS BT.
14" W.Oak bears S.9°E., 5.3 ft. scribed T28S R6W S25.
18" double W.Oak bears (?)19°W., 16,5 ft, scribed T28S R6W S26 CS BT.
4-way fence corner bears N.80°W., 15.0 ft.