

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Page 5705)

Set post cor. to secs. 13, 14, 23 and 24, from which
A Y.Oak 36" dia., bears N.21¼°W., 238 lks. dist.
A W.Oak 13" dia., bears N.47½°E., 139 lks. dist.
A Y.Oak 14" dia., bears S.88¾°E., 411 lks. dist.
No other tree near.

Claude Kerr, Dec. 1952 - C.S. File 41/101

Set 4 x 4 Oak post 4 ft. long for corner.
No BTs found. Marked 3 new BTs.
7" Oak bears N.5°E., 16.8 ft. scribed T28S R6W S13 BT.
6" Oak bears N.76°W., 27.0 ft. scribed T28S R6W S14 BT.
3" Oak bears S.5°E., 13.7 ft. scribed S24 BT.
I started at the cor. for secs. 23, 24, 25 and 26, chaining north on a random line. I checked on the ridge mentioned as 78 + 00 chs. north, and so chained 132 ft. past it. No O.B.T.s could be found so I ran west and hit the line fence. As the original notes showed a ridge 10 chs. West, I chained 660.0 ft. back East from the ridge and hit 19.8 ft. East of my point on the random line. The corner was set here. We checked this corner further by checking North to Roberts Creek which the notes call 6.00 chs. and checked closely.

C.G. Gale, Resident Engineer, OSHD - March 11, 1955 - C.S. File 41/345

This cor. formerly mkd. by a 4" x 4" Oak post, destroyed, Set 3/4" round iron pin x 30" long in a concrete block cast in the ground. A 4" x 4" post marked "SHRW" (State Highway Right of Way) set by corner. A new fence has been installed, wire mesh with steel posts. Fence corner is approx. corner. This corner is approx. 150 ft. South of the Dixonville County Road #16 and 165 ft. West of the Pacific Hwy. right of way centerline.

Present steel fence cor. bears N.82°W., 60 ft. approx., by Bill Paulin, Nov. 20, 1959.

Doug. County Surveyors Office - Randall Smith; S.J. Flause Aug. 1, 1984 - C.S. File 62/18-19

CORNER REPORT ONLY
Found - 18" x 18" concrete block 6" above ground with a 3/4" iron rod protruding 2" from center of concrete block. Continued next page

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

7" now a 8" W.Oak with a well healed double blaze bears N.5°E., 15.7 ft. (Rec. 16.8 ft. is a slope dist. to center of tree face height).
6" now a 9" W.Oak with a well healed single blaze bears N.80°W., 27.0 ft. (Rec. N.76°W.)
3" now a 7" B.Oak tree cut into and no scribing fd., bears S.13°E., 14.0 ft. (Rec. S.5°E., 13.7 ft.)
Monument lies approx. 150 ft. South of Co. Rd. #16 and approx. 165 ft. West of I-5
THIS MONUMENT WAS SET BY A METHOD OTHER THAN RECOMMENDED BY THE BLM MANUAL.

Fd Ok by Jeffery Whitson, L.S. #2361 - For: Federal Aviation Administration - Dec. 1993 - M 118-25

Fd. Ok by Greg Lang, 2/1999 - 1999-0027

2