

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 14 Pages 5706-07)

-----  
Set post cor. to secs. 11, 12, 13 and 14, from which  
The point of a circular rock 2½ ft. high and 5½ ft. dia., at base bears S.45°E., 28 lks. dist.  
The top point of a rock, 3 ft. high and 8 ft. dia., at base, bears S.86°W., 140 lks. dist.  
The East point of rock 7 ft. high and 8 ft. x 16 ft. bears N.12°W., 1282 lks. dist.  
There are 8 to 10 smaller rocks, 9 chs. SE. of it.  
Made mound of rock.

Doug. County Surveyors Office - Byron and Crew - Feb. 20, 1962  
C.S. File 52/108; M 23-18

-----  
Found - High pointed rock bearing object per GLO notes of 1853  
Set 3/4" Iron rod flush.  
PK nail 10 ft. East of edge white line.  
PK nail 0.5 ft. West of edge white line.  
3/4" I.R. on East R/W line of State Highway.

Doug. County Surveyors Office - Randall Smith; Stephen Flauser  
July 26,27, 1984 - C.S. File 62/18-18

-----  
Found - 3/4" Iron rod 18" below ground.  
7 ft. high and 8 ft. x 16 ft. rock outcrop, East point bears N.12°W., 846.12 ft.  
A 3/4" I.R. protruding 6" above ground and 6" West of East R/W fence of I-5 bears N.88¾°E., 165.49 ft. (Rec. S.89°50'E., 165.62 ft.)  
PK nails per Byron not found, probably lost due to A/C overlay on I-5.  
New Accessories:  
5/8" I.Rod with an alum. cap stamped "BO 1 1984" set flush with ground bears N.45°E., 25.0 ft.  
5/8" I.Rod with an alum. cap stamped "BO 2 1984" set flush with ground bears S.45°E., 25.0 ft.  
Cor. lies in median strip between the north & south bound lanes of I-5.

Fd. Ok by D. Bentz, 5/94 - 1994-0048.  
Fd. OK by O.D.O.T. June 1999 - M132-10 A&B  
Fd. OK by R. Brown, June 2001 - M137-12  
Fd. IR & accessories per 1984 ren., K. DeGroot, 6/2014 M166-12

