

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 631700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. 36 only, T27-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
 A Y.Oak 12" dia. bears N.11°W., 46 lks. dist.
 A Y.Oak 14" dia. bears N.46°E., 63 lks. dist.

Milo E. Godfrey, Deputy - Wm. Stoffel; M. Stone; M. Darby
May, 1964 - C.S. File 49/79

Found - 14" B.Oak N.11°W., 30.4 ft. opened & found good
 reverse scribing. Did not found NE tree.
Set - Brass cap at cor. mkd. County Surveyors Office 1964
 T 27S R6 W ¼ S 36
New BTs - 13" B.Oak N.50°E., 34.9 ft. mkd. ¼ S36 CS BT.
 17" B.Oak N.77°E., 25.5 ft. mkd. ¼ S36 CS BT.
Corner lies on very steep N.W. slope above S. Umpqua River.
(This corner is on N. line T28S R6W)

Douglas Co. Surveyors Office - Randall W. Smith, Stephen J.
Flause; July 20, 1993 - C.S. File 64/46-3

Found - 2½" dia. Brass Cap on a 1¼" O.D iron pipe
 protruding 14" above ground. (1964 Godfrey)
 12" now 12" dia dead Oak with a previously opened
 blaze reverse scribing found, bears N.11°W.,
 30.4 ft. (orig. BT)
 13" now 16" dia. B.Oak with a fully healed single
 blaze, bears N.50°E., 34.9 ft. (1964 Godfrey)
 17" now 19" dia. B.Oak with a fully healed double
 blaze, bears N.77°E., 25.5 ft. (1964 Godfrey)
New - 7" dia. W.Oak, double blazed and scribed "¼ S36 CS
 BT" bears N.10½°E., 39.8 ft.
 11" dia. B.Oak, double blazed and scribed "¼ S36 CS
 BT" bears N.63°W., 29.2 ft.

Fd. DCSO Brass Cap 7/2022 J. Estabrook - 2022-0035