TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Township

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5648)

Set post corner to Tps. 28 and 29 South and between ranges 5 and 6 West, from which

A Y.Oak 24" dia., bears S.45°W., 130 lks.
A Y.Oak 24" dia., bears N.36°W., 315 lks.
A W.Oak 22" dia., bears N.84°E., 137 lks.
A Y.Oak 14" dia., bears S.41½°E., 201 lks.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - Sept/Oct. 1961 - C.S. File 49/64-15

Found - Orig. 22" now 28" W.Oak N.84°E., 84.0 ft. not 90.4 ft. We open and find good scribing.
Orig. 24" now 30" B.Oak snag, center rotted, no scribing, S.45°W., 85.8 ft.
Orig. NW BT standing, shows good scars.
Orig. SE BT not found.
We find 1" I.P. bearing N.80°E., 18.8 ft.

Set brass cap mkd: County Surveyors Office, 1961

```
R6W S36|S31     T28S
       S 1|S 6 R5W T29S
```

New BTs -10" W.Oak bears N.83°W., 12.5 ft. scribed S36 T28S R6W CS BT.
12" W.Oak bears S.36°W., 15.7 ft. scribed S1 T29S R6W CS BT.
8" W.Oak bears S.64°E., 21.0 ft. scribed S6 T29S R5W CS BT.
11" W.Oak bears N.30°E., 6.0 ft. scribed S31 T28S R5W CS BT.

(Fd. brass cap and all bearing trees OK, Oct. 11, 1973 C.S. 56/39-7)

DCSO-GIS Corner visitation - 6/2/2004 - Typed: 1/31/2011 - C.S. File 67/33-1

Monument - BC/IP - 1.25"
Comment - OK