

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec Cor for 24 & 25; 19 & 30 of T28-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5647)

-----  
Set post corner to secs. 19, 30, 24 and 25, from which  
A Laurel 30" dia., bears S.25°E., 9 lks. dist.  
A Y.Oak 8" dia., bears S.20°W., 29 lks. dist.  
A Y.Oak 8" dia., bears N.10°W., 63 lks. dist.  
A Y.Oak 10" dia., bears N.33°E., 41 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - M. Godfrey; S. Bilow - Feb. 20, 1958 - C.S. File 49/64-4

-----  
Found - 3 orig. BTs, check record bearing & distance.  
I open orig. NW BT & find good scribing "S24 T28".  
Other orig. BTs show old scars. I do not open.  
The NE BT now 20".  
The NW BT now 18".  
The Laurel S.25°E., now 48".  
I also find 14" B.Oak S.60°W., 19.5 ft. (Rec. S.20°W., 19.1 ft.) shows old scar. I believe it is the orig. SW BT.

Set Brass cap at cor. mkd. R S24|S19 R T28S County Surveyor's  
6 S25|S30 5 Office, 1958  
W W

New BTs - 16" B.Oak N.40°W., 43.5 ft. scribed S24 T28S R6W  
CS BT.  
Rescribe 48" Laurel S.25°E., 5.9 ft. S30 T28S R5W  
CS BT.  
Rescribe 14" B.Oak S.60°W., 19.5 ft. S25 T28S  
R6W CS BT.

Fd. OK, D. Baker, May 1991, M 113-32  
Fd. OK by K. DeGroot, Dec. 2001 - 2001-0102 A&B  
Fd. 1958 BC & accessories per ren. 6/2014 - M166-12 K. DeGroot