

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13; & 18 T28-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5646)

Set 1/4 sec. post, from which
A Y.Oak, 20" dia., bears N.8°25'E., 1638 lks.
A boulder 8 ft. x 5 ft. x 3 ft. high on top of ridge,
bears S.15 3/4°W., 630 lks.

Kris DeGroot - For: Smith Trust - 6/2014 - M166-12

Restored from an orig. bearing object by Elder & Gile in 1853
Set - A 1 1/4"x30" iron post, 6" below the ground, with a 2 1/2" brass cap mkd:

DOUGLAS COUNTY SURVEYOR

T28S

1/4
R | R
6 S13 | S18 5
W | W

2014

From which the original 1853 bearing object by Elder & Gile:
A boulder, 8'x5'x3' high, bears S.15°45'W., 415.80 ft (630 lks) - No mks visible.

Set - A 6" cotton-gin spike in top center of boulder & BT tag on face.

New RMs -

5/8" iron rod per M47-34 bears S.54°38'11"E. 1086.25 ft
A 3/4" iron rod per M7-29 bears S.14°16'37"W., 654.72 ft.

Set - A 5/8"x30" iron rod w/PC bears S.0°4'01"W., 633.47 ft.

Set - A 5"x8' treated wood post, 3' in ground, 2 ft North of corner with location tag

Corner falls in cow pasture, 52 ft. East of N-S fence line, on top of N-S ridge.