

TOWNSHIP 28 RANGE 07½ POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 18; & 13, T28-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, Contract #57 dated April 12, 1855 (DCSO records, Vol. 14 Page 5790)

-----  
Set ¼ sec. post, from which  
    A Fir 12" dia., bears N.63°E., 9 lks. dist.  
    A Fir 6" dia., bears N.34°W., 40 lks. dist.  
(Old ¼ post bears North 16.60 chains and East 3.37 chs. - Ford Survey)

GL0 resurvey by Mensch, 1924 - (DCSO records, Vol. 14 Pages 5915-16)

-----  
Intersect the point for ¼ sec. cor., located by measurement from the original bearing trees. The blazes are plain but marks are grown over.

At the exact corner point  
Set an iron post, 3 ft. long, 1 ins. diam., 28 ins. in the ground, with brass cap mkd:

¼  
S13 | S18  
      | R7½  
      1924

from which (original bearing trees)  
    A Fir 24" dia., bears N.63°E., 9 lks. dist. re-marked  
      ¼ S18 R7½ BT.  
    A Fir 10" dia., bears N.31°W. (not N.34°W.) 40 lks.  
      re-marked ¼ S 13 BT.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - May 1961 - C.S. File 52/79-7

-----  
Found - Brass cap at corner. NE BT now snag. NW BT OK.  
New BT - 12" W.Fir bears S.5°E., 13.5 ft. scribed ¼ S18 CSBT

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/14/1998 - C.S. File 66/2-32

-----  
Found - 2½" dia., brass cap on a 1" O.D. iron pipe protrudes 5" above ground, properly marked. Note: brass cap orientated Southeast.

Orig. NE BT now gone.  
6" Fir, now rotted to ground stump, scribing found "4S13BT" bears N.31°W., 26.4'. (Agrees with ren records) OBT

1961 DCSO BT now rotted Fir remains near record "S.5°E., 13.5 ft." No scribing found.

New BTs- 6" dia., D.Fir, double blazed and scribed "¼ S18 CS BT" bears S.61°E., 4.8'.

(Cont. next page)

TOWNSHIP 28 RANGE 07½ POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18; S13 T28-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

10" dia., G.Fir, double blazed and scribed "¼ S13 CS BT" bears N.41½°W., 21.0'.  
8" dia., G.Fir, double blazed and scribed "¼ S13 CS BT" bears S.87°W., 28.5'.  
Corner lies approx. S.45°W., 100' from end of road.

FD. Ok by D. Edwards, 8/2009 - M159-62