

TOWNSHIP 28 RANGE 07½ POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. 7 & 18; 12 & 13, T28-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #57 dated April 12, 1855 (DCSO records, Vol. 14 Page 5786)

Set post cor. secs. 7, 18, 12 and 13, from which
A Chinquapin, 6" dia., bears N.12°W., 17 lks.
A Fir, 10" dia., bears N.42°E., 34 lks.
A Fir, 12" dia., bears S.80°W., 10 lks.
A Laurel, 12" dia., bears S.4°E., 13 lks.

GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pages 5914-15)

Intersect the point for cor. of secs. 7, 12, 13, and 18, located by record bearing and measurement from the SW original bearing tree on which the marks are legible. The NE., SE., and NW. bearing trees ahve been destroyed. At the exact cor. point
Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd:

T28S	
R8W	R7½W
<u>S12</u>	<u>S7</u>
S13	S18
1924	

from which (new Bearing trees)
A Fir 30" dia., bears N.17°E., 59 lks. dist., mkd. T28S R7½W S7 BT.
A Dogwood 7" dia., bears S.74°E., 19 lks. dist., mkd. T28S R7½W S18 BT.
A Fir 36" dia., bears N.26°W., 52 lks. dist., mkd. T28S R8W S12 BT.
Original SW bearing tree, a Fir, 36" dia., bears S.80°W., 10 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - May 1961 - C.S. File 52/79-5

Found - Brass cap at corner.
36" Fir S.80°W., 6.6 ft. alive & in good condition.
Dogwood, down & dead, S.74°E., 12.5 ft. showing old scribing.
30" Fir, dead snag, N.17°E., 38.9 ft.
36" Fir uprooted & dead, N.26°W., 34.3 ft.
New BT - 18" D.Fir N.54½°W., 77.0 ft. scribed T28S R8W S12 CS BT.

(Cont. next page)

TOWNSHIP 28 RANGE 07½ POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7 & 18; 12 & 13 T28-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/13/1998 - C.S. File 66/2-30

Found - 2½" dia., brass cap on a 2" O.D iron pipe, protrudes 8" above ground, properly marked. 1924
A 41" dia., D.Fir with healed blazes, bears S.80°W., 6.6'. Agrees w/rec. OBT
18" now 22" dia., 10' high rotted D.Fir snag with a partially healed blaze, scribing visible "T28S R8W S12 CS BT", bears N.54½°W., 77.0'. Agrees w/rec. 1961
New BTs- 11" dia., Cedar, double blazed & scribed "T28S R8W S12 CS BT" bears N.57°W., 43.2'.
5" dia., D.Fir, double blazed & scribed "X CS BT" bears N.64½°E., 8.4'

FD. Ok by D. Edwards, 8/2009 - M159-62

Fd. BC & 3 BTs and steel post 6/2014 by R. Rice, C.S. file 65/84-5