

TOWNSHIP 28 RANGE 07½ POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6; & 1, T28-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Mensch, 1924 (DCSO records, Vol. 14 Page 5912)

Apportioned distance,
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, with brass cap mkd: ¼

S1 | S6
 | R7½
 1924

from which

A Chinquapin 8" dia., bears N.87°E., 26 lks. dist. mkd.
¼ S6 R7½ BT.

A Fir 12" dia., bears N.78°W., 75 lks. dist., mkd.
¼ S1 BT.

Note: At ¼ sec. cors. referring to T28S R7½W., the marks R7½
are placed upon corners and bearing trees to distinguish
these cors. referring to old secs. of the same designation of
T28S R7W.

Doug. County Surveyors Office - James Byron, Deputy - Milo
Godfrey; Clete Putnam - May 1961 - C.S. File 52/79-12

Found - Brass cap and NW BT, now stump. SE BT is OK.
New BT - 17" R.Fir bears N.70°W., 37.0 ft. recently scribed
¼ S1 and other scribing.

Fd. OK, Nov. 1985 by R. Geisler - M 90-79