

TOWNSHIP 28 RANGE 07½ POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Mensch, 1924 (DCSO records, Vol. 14 Pg. 5853

Intersect W. bdy. of orig. sec. 6.

At this point

Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for NE cor. of T.28S R7½W, with brass cap mkd:

S 6	
T28S	
R7½W	1924

from which

A Fir 24" dia., bears S.24½°W., 46 lks. dist. mkd. T28S R7½W S 6 BT.

A Fir 12" dia., bears S.65½°W., 31 lks. dist. mkd. T28S R7½W., S6 BT.

Ford's original standard cor. of T.28S Rs. 7 and 8 W., re-established as NW cor. of T28S R7W bears N.0°41'E., 8.78 chs.

H. L. Eppstein - Wit: B.A. Lane; Fitzpatrick; Hollis Green
June, 1930 - M 1-73; C.S. Files 14/44 & 14/59; Vol. 4 Pg. 11

Found Standard Gov't post set by Mensch in 1924 - S6 R7½

From which

R.Fir 24" dia., bears S.23°W., 30.0 ft.

R.Fir 12" dia., bears S.63°W., 20.0 ft.

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - May, 6, 1997 - C.S. 64/74-27

Mon. Fd.- 3½" dia. Brass cap 3" O.D. iron pipe, protrudes
6" above ground. 1924

Accessories Fd.-

24" now 24" dia. 3½' high rotted D.Fir stump,
with scribing visible "T28S R7½W S6", bears
S.23°W., 30' (agrees with 1930 DCSO rec.)
1924 OBT

1924 D.Fir bearing S.65½°W., 20.5' now gone.

31" dia. I.Cedar, with a fully healed single
blaze, bears S.16°E., 52.7' (BLM BT tag reads
N.14°W., 52.7' CS 2-61) source unknown.

New Accessories -

8" dia. B.Oak, double blazed and scribed "T28S
R7½W S6 CS BT", bears N.84°E., 25.3'.

11" dia. I.Cedar, double blazed and scribed "T28S
R7½W S6 CS BT", bears S.86°W., 2.4'.

3" dia. D.Fir, double blazed and scribed "X BT",
bears S.40°W., 15.4'.

Cor. lies in a N-S fence line 10' So. of a fence running East