

TOWNSHIP 28 RANGE 07½ POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION E. 1/4 Sec. 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Mensch, 1924 (DCSO records, Vol. 14 Pg. 5934)

A Point 0.33 chs. East of Hathorn's ¼ sec. cor. of secs. 25 and 30, on the E. bdy. of T28S R8W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor. of sec. 30 only, T28S R7½W, with brass cap mkd:

¼S30:

R7½:

1924

from which

A B.Oak 10" dia., bears N.24°W., 54 lks. mkd. ¼ S30 R7½ BT
No other tree in sec. 30 available, no stones available for mound.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 2/7/2001 - C.S. File 66/19-30

Found - 1924 GLO brass cap/iron pipe, protrudes 12" out of ground.

1924 GLO BC/IP T28SR7½W W ¼ S30, protrudes 6" out of ground bears West 21.8 ft. (agrees w/rec.)

10" now 16" dia., B.Oak with a fully healed blaze, bears N.24°W., 34.8 ft. (rec. N.24°W., 35.6 ft., dist. is a slope meas.) 1924

New - 35" dia., B.Oak with a fully healed blaze facing W¼ bears N.13°E., 59.0 ft. (1923 DCSO BT to W¼)

22" dia., W.Oak double blazed & scribed "¼ S30 CS BT" bears S.63½°W., 28.2 ft.

See last Pg for pictures.

TOWNSHIP 28 RANGE 07½ POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION E. 1/4 Sec. 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

