

PRIMARY CORNER DESCRIPTION Sec Cor. for 19 & 30 only (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO subdivision R7½W by Mensch, 1924 (DCSO records, Vol. 14 Pages 5935-36)

Intersect the W. bdy. of T28S R7W, 17.20 chains S.1°42'W. from the cor. of secs. 19 and 30. At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd: T28S

S19
S30
R7½W
1924

from which

A Fir 12" dia., bears S.70°W., 16 lks. dist. mkd. T28S R7½W S30 BT.

A Fir 20" dia., bears N.57°W., 27 lks. dist., mkd. T28S R7½W S19 BT.

Doug. County Surveyors Office - James W. Byron, Deputy Milo Godfrey; Clete Putnam - May 1961 - C.S. File 52/79-4

Found - Brass cap at cor. and NW BT OK., shows good scar. New BT - 6" R.Fir bears N.39½°E., 35.0 ft. scribed S30 CSBT.

Doug. County Surveyors Office - Randall Smith, Deputy - Stephen Flause - June 26, 1985 - C.S. File 62/28-10

Found - 1924 GLO survey disk on an I.P., firmly set, and protruding 4" above ground.

20" now a 20" dia., 35 ft. high D.Fir snag, with a single blaze, fully healed, bears N.57°W., 17.8 ft. Agrees w/record. (Orig.)

6" now a 19" dia., D.Fir with a double blaze, fully healed bears N.39½°E., 35.0 ft. (Agrees w/rec. 1961) Bearing tree on wrong side of range line according to Manual of Survey Instructions.

No evidence found of orig. SW BT.

New BTs - 19" D.Fir double blazed and scribed "T28S R7½W S19 CS BT" bears N.44½°W., 43.4 ft.

13" D.Fir double blazed and scribed "T28S R7½W S30 CS BT" bears S.42½°W., 77.0 ft.

4" W.Oak double blazed and scribed "X BT" bears S.2°W., 44.4 ft.

Corner lies near the intersection of two dim track jeep roads in small clearing.