

TOWNSHIP 28 RANGE 07½ POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 19 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Mensch, 1924 (DCSO records, Vol. 14 Page 5932)

A point 1.50 chains East of Hathorn's ¼ sec. cor. of secs. 19 and 24, on E. bdy. of T28-8. Point for ¼ sec. cor. falls on surface bedrock, impracticable to set iron post; therefore, at the exact cor. point: I mark a cross (X) on the bedrock, over which set a basalt stone, 20" x 10" x 4" in mound of stone and earth, for ¼ sec. cor. of sec. 19 only, T28S R7½W, marked "¼" on W. face; from which:

A B.Oak 5" dia., bears N.32°W., 81 lks. dist. mkd. ¼ S19 R½ BT.

A Fir 10" dia., bears S.7½°W., 130 lks. dist., mkd. ¼ S19 R7½ BT.

Doug. County Surveyors Office - James W. Byron, Deputy
Milo Godfrey; Clete Putnam - May 1961 - C.S. File 52/79-9

Found - Both BTs OK, show good scars. I do not open.

Find stone at corner, but do not find "X".

We drill hole and set ½" x 12" I.Rod at corner and set 3/4" x 30" Iron rod alongside. Rods set in concrete.